


Let's Make Things Last

#### Datasheet A94 - PS.EVOH.PE



The A94 sheet is a high barrier multilayer PS.EVOH.PE sheet suitable for all range of products which require high barrier for oxygen, gasses, aromas as well as a moisture barrier. The A94 sheet is suitable for aseptic packaging and hot fill up to 85 °C. The sheet has excellent machinability on standard thermoforming equipment designed for PS use. Multiple top and bottom heating is required with a forming tool with PE adapted plug assist and appropriate cooling, and a well-adjusted cutting tool.

### **G**eneral

Composition	PS.EVOH.PE
Colour	Transparent or coloured
Thickness range	250 - 2000 μm
Width	80 - 1250 mm

#### ${\sf P}_{\sf hysical}$

Specific weight	1.03 – 1.05 g/cm³
-----------------	-------------------

### $\mathsf{T}_{\mathsf{hermal}}$

Dimensional stability	< 5% (30min @ 130 °C)
Thermoforming range	PE : 120 °C ± 5 °C PS : 140 °C ± 10 °C

## Barrier

OTR (20 °C – 65%RH)	max 0.3 cc/m².24h.atm
MVTR (38 °C – 90%RH)	max 2.3 g/m².24h

<sup>\*</sup> Typical values for a 1 mm sheet with 3% EVOH (32mol% ethylene) and 7% PE.

# **F**eatures

- Excellent organoleptic properties for PE as food contact layer
- Suitable for processed cheese, liquids, desserts, fruit compote, juices, tomato based products
- Permanent or easy peel seal against aluminium or plastic lidding material

Storage conditions and expected product shelf life: it is recommended to store the reels in the original packaging at [10-35]°C – max 65% RH and protected from sunlight to guarantee a product life of 12 months

Sheets are manufactured under industrial accepted standards for cGMP. Sheet is composed with components in compliance with EU regulations. Cobelplast is certified ISO 9001:2015, ISO 14001:2015 & BRC/IoP v6

Cobelplast nv disclaims responsibility for results of use of this information or any product, method or apparatus mentioned herein. It is the user's responsibility to make and be guided by his own tests in determining suitability of any product, method or apparatus for this purpose. No warranty is made of the merchantability or fitness of any product; and nothing herein waives any of the Seller's conditions of sale.

Cobelplast NV Antwerpse steenweg 14 9160 Lokeren – Belgium Tel: +32 (0)9 340 99 11 Mail: info@cobelplast.be

Issue date: 13/03/2024 Expiry date: 12/03/2027

